

# Used machines offer

## NEW STRATOS F40I-27 VESN-490 - NEW Spre



Offer number: UM3434926



Brand: Schmidt  
 Mat.-Nr.: 1369905-4  
 Year of manufacture: 2023  
 Serialnumber: S2F33848  
 Running hours: 0 h  
 Mileage: 0 km  
 Condition: Class 5+  
 Location: Germany  
 79837 St. Blasien

Price: **On request**

Stratos spreader are compatible with most carrier vehicles. The intuitive operation and outstanding performance of the Stratos guarantees an intelligent and efficient winter maintenance operation.

### Gallery



### Equipment

<b>Basic machine</b>	
209717	STRATOS F 40 for U500/527/530 K
<b>Container assemblies</b>	
905874	Twin screw conveyor and double chamber container
930649	Protective grille 40x40 mm, steel (for S 35K - 50K, F40)
963335	Folding roof professional (for 35K - 60)
533125	Standard color RAL 2011
991973	Auger cover (series)
739911	Driving wind spotlight (standard in orange RAL2011) *
539357	Stairs made of stainless steel (standard for stainless steel)
<b>Wet salt modules</b>	
402464	Wet salt system 1,760 liters (for 35K - 50K)
560502	Wet salt system EN15597-1 Min/Max level switch and level indicator
912321	Wet salt coupling Storz 2"
718248	Float switch maximum level, 4-pin (part of 560502)
991673	Check valve (option for Storz 2")

614878	Float switch minimum level (part of 560502) Automatic water pump switch-off when running dry Yes
<b>Drive</b>	
474903	Drive via vehicle hydraulics („V“)
918914	Hydraulic couplings U2 U300-U500 from July 1, 2009, ISO16028 P=Gr.19(F) R=Gr.19(M)
<b>Steering</b>	
968675	Evolution Smart „ES“ control system, with color touchscreen
378372	RS232 splitter cable for EP/ES (for EN16330 control panel cable)
271071	ThermoLogic (for ES) mounted at the rear of the device
870069	Interface sockets for control panel and spreader, according to EN16330, Unimog with ES6
333195	Control panel holder EC/EP/ES Unimog Euro 6 (DH3)
<b>Distribution system</b>	
454796	Spreading plate „490“ (spreading width 2 - 8/10 m)
143517	Optical spread control sensor (for EC, EP and ES)
438459	Spreading control via LED lamp (red or white)
Spreading width	Spreading width = 2-10m.
Diffuse control via headlights	White
<b>Storage and fastening parts</b>	
260260	Ball point frame high „K10“, for Unimog U500/527/530 K
375213	Base frame blasted and powder-coated, RAL7021
977319	Storage feet (4 pcs.) 3 tons, crank drive in the middle, including side supports
<b>Special equipment</b>	
757833	Cover, blue (RAL5002)
440333	Rotating beacon with LED lamp
865267	Tail light (LED)
300906	Warning foil red and white, at the rear of the machine
995056	Marking „Winter Service“ (German)
756782	Splash guard 2,200 mm
<b>Other options</b>	
Length of spreading plate suspension with loaded spreader	1180-1750 (490) and 1230-1750(660) or 1180-1450(Integral)
Vehicle type	U527/530=200/220KW
Wheelbase	3350mm Euro-6/C405.202
Speed measurement	Electronically from the Unimog speedometer
Vehicle voltage	24 volts
Vehicle connector	15-pin ABS connector ISO 12098

## Contact

Artur Maciejewski  
Used Machines Sales Manager



© Aebi Schmidt Group  
www.aebi-schmidt.com

Aebi Schmidt Holding AG  
CH-8050 Zurich, Switzerland

All rights reserved. Technical data is subject to change.  
Illustrations are not binding. Errors and amendments excepted.

Document created on 14.12.2023

